



Powering Business Worldwide

# Internal Replacement Battery Cartridge (RBC) for 9SX1500, 9SX1500G, and SU1500XLCD UPS Systems

MODEL NUMBER: 744-A4312



UPS backup battery cartridge replaces the expired or aging internal battery in your Eaton 9SX or Tripp Lite series SmartOnline UPS system.

## Features

### UPS Replacement Battery Cartridge for Select Online Tower UPS Systems

This UPS backup battery replacement is compatible with 9SX1500, 9SX1500G, and SU1500XLCD UPS systems. Eaton UPS batteries have an expected lifespan of three to five years, so you should take proactive steps to avoid a dead battery and ensure continuous uptime.

### Comes Pre-Wired for Quick, Easy Installation

The sealed lead acid (SLA) 744-A4312 internal battery cartridge is hot-swappable, allowing you to install it without powering down any connected equipment. Built to function in a wide range of operating temperatures, the 744-A4312 has been carefully screened and certified to restore your UPS system's runtime performance to its original specifications. It is leakproof, requires no maintenance and comes pre-wired for quick and easy installation in your UPS system.

## Specifications

OVERVIEW	
UPC Code	786689575601
INPUT	
Input Phase	Single-Phase
BATTERY	
Battery Type	Valve Regulated Lead Acid (VRLA)
Battery Replacement Description	Hot-swappable, user replaceable battery. UPS requires 1 Replacement Battery Cartridge.
Hot Swap Battery	Yes

## Highlights

- Replacement battery backup for 9SX1500, 9SX1500G, or SU1500XLCD UPS systems
- Carefully screened and certified to restore UPS runtime to original specs
- Leakproof internal battery cartridge requires no regular maintenance
- Ships ready for immediate UPS installation to prevent downtime

## System Requirements

Compatible with the 9SX1500, 9SX1500G, and SU1500XLCD (2023 redesign) UPS system

## Package Includes

744-A4312 Internal Replacement Battery Cartridge



Powering Business Worldwide

<b>PHYSICAL</b>	
Unit Dimensions (hwd / in.)	5.700 x 16.400 x 16.900
Unit Weight (lbs.)	25.4
Unit Weight (kg)	11.52
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32° to 104°F (0° to 40°C)
<b>APPLICATIONS</b>	
Used With	9SX1500, 9SX1500G, SU1500XLCD (2023 redesign model)
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Certifications	UL Listed; cUL Listed
Product Compliance	FCC (USA); CE (Europe)

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.