

Specifications

Eaton EMA112-10



Eaton Managed PDU, 1PH, 0U, NEMA 5-15P input, 10 ft cord, 1.44kW, 12A, 120V, 16 Outlets (16) 5-15R

General specifications

PRODUCT NAME	Eaton managed PDU
CATALOG NUMBER	EMA112-10
PRODUCT LENGTH/DEPTH	66.5 in
PRODUCT HEIGHT	2.56 in
PRODUCT WIDTH	2.05 in
PRODUCT WEIGHT	13 lb
COMPLIANCES	RoHS Compliant TAA Compliant
CERTIFICATIONS	UL Listed



Powering Business Worldwide

Product specifications

FORM FACTOR	0U (Vertical)
OUTLET CONTROL	Yes
PHASE	Single-phase
WATTAGE	1.44 kW max
AMPERAGE RATING	12A
INPUT VOLTAGE	120V
INPUT CONNECTION	5-15P
OUTLETS	(16) 5-15R
CORD LENGTH	10 ft
FREQUENCY RATING	50-60 Hz
SERIAL INTERFACE	RS-232
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)

Resources

CERTIFICATION REPORTS	Eaton ePDU certificate of volatility Eaton RoHS Declaration of Conformity: ePDU G3
DRAWINGS	Eaton ePDU Managed eMA112-10 technical drawing Eaton Advanced Monitored and Managed ePDU visio stencil
MANUALS AND USER GUIDES	Eaton Double-wide G3 ePDU installation and connectivity quick start guide Eaton ePDU G3 operations manual Eaton ePDU G3 1U and 2U installation addendum Eaton ePDU G3 replace and configure eNMC module Eaton ePDU G3 instruction set - system objects
SERVICE AND TROUBLESHOOTING	EMA112-10 eNMC replacement configuration file

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

