

Specifications

Eaton EMA333-10

Eaton Managed PDU, 3PH, 0U, L21-30P input, 10 ft cord, 8.64kW, 24A, 120/208V, 28 Outlets (21) C13 (6) C19 (1) 5-20R, TAA



General specifications

PRODUCT NAME	Eaton managed PDU
CATALOG NUMBER	EMA333-10
UPC	743172078902
PRODUCT LENGTH/DEPTH	72 in
PRODUCT HEIGHT	2.56 in
PRODUCT WIDTH	2.05 in
PRODUCT WEIGHT	20.3 lb
WARRANTY	3 year
COMPLIANCES	RoHS Compliant TAA Compliant
CERTIFICATIONS	UL Listed
PRODUCT TYPE	Managed PDU



Powering Business Worldwide

Product specifications

FORM FACTOR	0U (Vertical)
OUTLET CONTROL	Yes
PHASE	Three-phase
WATTAGE	8.64 kW max
AMPERAGE RATING	24A
INPUT VOLTAGE	120/208V
INPUT CONNECTION	L21-30P
OUTLETS	(1) 5-20R, (21) C13 Outlet grip, (6) C19 Outlet grip
CORD LENGTH	10 ft
FREQUENCY RATING	50-60 Hz
SERIAL INTERFACE	RS-232
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)

Resources

CERTIFICATION REPORTS	Eaton ePDU certificate of volatility
	Eaton RoHS Declaration of Conformity: ePDU G3
DRAWINGS	Eaton Advanced Monitored and Managed ePDU visio stencil
	Eaton ePDU Managed eMA333-10 technical drawing
MANUALS AND USER GUIDES	Eaton Double-wide G3 ePDU installation and connectivity quick start guide
	Eaton ePDU G3 operations manual
	Eaton ePDU G3 instruction set - system objects
	Eaton ePDU G3 replace and configure eNMC module
	Eaton ePDU G3 1U and 2U installation addendum
SERVICE AND TROUBLESHOOTING	EMA333-10 eNMC replacement configuration file
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - EMA333-10

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.