

Specifications

Eaton EMAT08-10

Eaton Managed PDU, 1PH, 1U, NEMA 5-15P input, 10 ft cord, 1.44kW, 12A, 120V, 8 Outlets (8) 5-15R



General specifications

PRODUCT NAME	Eaton managed PDU
CATALOG NUMBER	EMAT08-10
UPC	743172082657
PRODUCT LENGTH/DEPTH	19 in
PRODUCT HEIGHT	8 in
PRODUCT WIDTH	1.69 in
PRODUCT WEIGHT	6.9 lb
WARRANTY	3 year
COMPLIANCES	Contact Manufacturer
CERTIFICATIONS	UL Listed
PRODUCT TYPE	Managed PDU



Powering Business Worldwide

Product specifications

FORM FACTOR	1U
OUTLET CONTROL	Yes
PHASE	Single-phase
WATTAGE	1.44 kW max
AMPERAGE RATING	12A
INPUT VOLTAGE	120V
INPUT CONNECTION	5-15P
OUTLETS	(8) 5-15R
CORD LENGTH	10 ft
FREQUENCY RATING	50-60 Hz
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)

Resources

CERTIFICATION REPORTS	Eaton ePDU certificate of volatility
	Eaton RoHS Declaration of Conformity: ePDU G3
DRAWINGS	Eaton Advanced Monitored and Managed ePDU visio stencil
	Eaton ePDU Managed EMAT08-10 technical drawing
MANUALS AND USER GUIDES	Eaton ePDU G3 operations manual
	Eaton ePDU G3 instruction set - system objects
	Eaton Double-wide G3 ePDU installation and connectivity quick start guide
	Eaton ePDU G3 replace and configure eNMC module
	Eaton ePDU G3 1U and 2U installation addendum
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - EMAT08-10

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

