

Specifications

Eaton EMI104-10

Eaton Metered Input PDU, 1PH, 0U, L6-30P input, 10 ft cord, 5.76kW, 24A, 200-240V, 42 Outlets (36) C13 (6) C19



General specifications

PRODUCT NAME	Eaton metered input PDU
CATALOG NUMBER	EMI104-10
UPC	743172050458
PRODUCT LENGTH/DEPTH	2.05 in
PRODUCT HEIGHT	66.5 in
PRODUCT WIDTH	2.1 in
PRODUCT WEIGHT	15.54 lb
WARRANTY	3 year
COMPLIANCES	TAA Compliant
CERTIFICATIONS	UL Listed
PRODUCT TYPE	Metered input PDU



Powering Business Worldwide

Product specifications

FORM FACTOR	0U (Vertical)
OUTLET CONTROL	No
PHASE	Single-phase
WATTAGE	5.76 kW max
AMPERAGE RATING	24A
INPUT VOLTAGE	200-240V
INPUT CONNECTION	L6-30P
OUTLETS	(36) C13 Outlet grip, (6) C19 Outlet grip
CORD LENGTH	10 ft
FREQUENCY RATING	50-60 Hz
ETHERNET INTERFACE	Yes
SERIAL INTERFACE	RS-232
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)

Resources

BROCHURES	Eaton ePDU G3 brochure
CERTIFICATION REPORTS	Eaton RoHS Declaration of Conformity: ePDU G3
DRAWINGS	Eaton ePDU G3 Metered Input EMI104-10 technical drawing Eaton Metered Input PDU Visio stencils
MANUALS AND USER GUIDES	Eaton ePDU G3 instruction set - system objects Eaton ePDU G3 EMP installation and connection quick start guide Eaton ePDU G3 operations manual Eaton ePDU G3 installation and connectivity quick start guide
SERVICE AND TROUBLESHOOTING	ePDU G3 firmware and MIBs EMI104-10 eNMC replacement configuration file
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - EMI104-10
WARRANTY GUIDES	Eaton limited warranty for rackmount PDUs

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

