

# Specifications

## Eaton EMI310-10

Eaton Metered Input PDU, 3PH, 0U, L21-30P input, 10 ft cord, 8.64kW, 24A, 120/208V, 37 Outlets (30) C13, (6) C19, (1) 5-20R



### General specifications

<b>PRODUCT NAME</b>	Eaton metered input PDU
<b>CATALOG NUMBER</b>	EMI310-10
<b>UPC</b>	743172050410
<b>PRODUCT LENGTH/DEPTH</b>	2.05 in
<b>PRODUCT HEIGHT</b>	66.5 in
<b>PRODUCT WIDTH</b>	2.1 in
<b>PRODUCT WEIGHT</b>	17.61 lb
<b>WARRANTY</b>	3 year
<b>COMPLIANCES</b>	TAA Compliant
<b>CERTIFICATIONS</b>	UL Listed
<b>PRODUCT TYPE</b>	Metered input PDU



Powering Business Worldwide

## Product specifications

<b>FORM FACTOR</b>	0U (Vertical)
<b>OUTLET CONTROL</b>	No
<b>PHASE</b>	Three-phase
<b>WATTAGE</b>	8.64 kW max
<b>AMPERAGE RATING</b>	24A
<b>INPUT VOLTAGE</b>	120/208V
<b>INPUT CONNECTION</b>	L21-30P
<b>OUTLETS</b>	(1) 5-20R, (30) C13 Outlet grip, (6) C19 Outlet grip
<b>CORD LENGTH</b>	10 ft
<b>FREQUENCY RATING</b>	50-60 Hz
<b>ETHERNET INTERFACE</b>	Yes
<b>SERIAL INTERFACE</b>	RS-232
<b>OPERATING TEMPERATURE</b>	0° to 60°C (32° to 140°F)

## Resources

CERTIFICATION REPORTS	<a href="#">Eaton RoHS Declaration of Conformity: ePDU G3</a>
DRAWINGS	<a href="#">Eaton ePDU G3 Metered Input EMI310-10 technical drawing</a>
	<a href="#">Eaton ePDU G3 EMP installation and connection quick start guide</a>
MANUALS AND USER GUIDES	<a href="#">Eaton ePDU G3 operations manual</a>
	<a href="#">Eaton ePDU G3 installation and connectivity quick start guide</a>
	<a href="#">Eaton ePDU G3 instruction set - system objects</a>
SERVICE AND TROUBLESHOOTING	<a href="#">EMI310-10 eNMC replacement configuration file</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - EMI310-10</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

